

# Jerez

| Number | Colour       | 89 | Width mm |      |      | Light Properties |     |     | Solar Properties |     |     | Light Fastness | Gtot - value | FC - value |
|--------|--------------|----|----------|------|------|------------------|-----|-----|------------------|-----|-----|----------------|--------------|------------|
|        |              |    | 127      | 2300 | 3000 | R                | T   | A   | R                | T   | A   |                |              |            |
| 1069   | white        | ✓  | ✓        | ✓    |      | 69%              | 19% | 12% | 63%              | 22% | 15% | 5-6            | >0,45        | >0,80      |
| 9154   | light grey   | ✓  | ✓        | ✓    |      | 59%              | 14% | 27% | 52%              | 18% | 30% | 5-6            | >0,45        | >0,80      |
| 2275   | sand         | ✓  | ✓        | ✓    |      | 61%              | 16% | 23% | 56%              | 19% | 25% | 5-6            | >0,45        | >0,80      |
| 2337   | brown/nut    | ✓  | ✓        | ✓    |      | 42%              | 19% | 39% | 36%              | 22% | 42% | 5-6            | >0,45        | >0,80      |
| 9155   | mid grey     | ✓  | ✓        | ✓    |      | 18%              | 13% | 69% | 14%              | 17% | 69% | 5-6            | >0,45        | >0,80      |
| 2294   | nut          | ✓  | ✓        | ✓    |      | 44%              | 17% | 39% | 38%              | 20% | 42% | 5-6            | >0,45        | >0,80      |
| 9125   | slate        | ✓  | ✓        | ✓    |      | 13%              | 11% | 76% | 10%              | 14% | 76% | 5-6            | >0,45        | >0,80      |
| 2330   | honey        | ✓  | ✓        | ✓    |      | 43%              | 18% | 39% | 38%              | 21% | 41% | 5-6            | >0,45        | >0,80      |
| 2295   | chocolate    | ✓  | ✓        | ✓    |      | 27%              | 13% | 60% | 21%              | 17% | 62% | 5-6            | >0,45        | >0,80      |
| 5176   | night blue   | ✓  | ✓        | ✓    |      | 18%              | 12% | 70% | 13%              | 16% | 71% | 5-6            | >0,45        | >0,80      |
| 4139   | spring green | ✓  | ✓        | ✓    |      | 45%              | 16% | 39% | 41%              | 19% | 40% | 5-6            | >0,45        | >0,80      |
| 4140   | petrol       | ✓  | ✓        | ✓    |      | 19%              | 16% | 65% | 13%              | 20% | 67% | 5-6            | >0,45        | >0,80      |

All printed colours and textures only provide orientation and are not reference pattern.

Usable for Roller / Vertical / Pleated / Panel Track  
 Colour Range 26 (12 / 14)  
 Composition 100 % PES  
 Width 89 / 127 / 2300 / 3000 mm  
 Cutting Process hot  
 Processing Direction warp


Weight 150 g/m2  
 Thickness 0,35 mm  
 Moisture proofed yes  
 PVC free yes  
 Halogen free yes  
 OekoTex yes



Teflon



suitable for workstations



B semi-transparent



Standard 100 by Oeko-Tex®

R = Reflection, T = Transmission, A = Absorption · All light & solar properties have been tested internally or externally. · Gtot: measure total solar energy that passes through the glazing system and the fabric · Fc-value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g · All technical properties are subjected to production-related deviations. All fabrics are in line with the REACH regulation.