

# Lisboa Opac

Number	Colour	89	Width mm			Light Properties			Solar Properties			Light Fastness	Gtot - value	FC - value
			127	2300	3000	R	T	A	R	T	A			
1000	white-white	✓	✓	✓	✓	84%	0%	16%	71%	0%	29%	6-7	0,34	0,58
2304	ivory-white	✓	✓	✓		84%	0%	16%	71%	0%	29%	6-7	0,34	0,58
9030	light grey-white	✓	✓	✓	✓	84%	0%	16%	71%	0%	29%	6-7	0,34	0,58
9060	mouse grey-white	✓	✓	✓	✓	84%	0%	16%	71%	0%	29%	6-7	0,34	0,58
2272	sand-white	✓	✓	✓	✓	84%	0%	16%	71%	0%	29%	6-7	0,34	0,58
9092	anthracite-white	✓	✓	✓	✓	84%	0%	16%	71%	0%	29%	6-7	0,34	0,58
6025	yellow-white	✓	✓	✓		84%	0%	16%	71%	0%	29%	6-7	0,34	0,58
4125	light green-white	✓	✓	✓		84%	0%	16%	71%	0%	29%	6-7	0,34	0,58
5053	blue-white	✓	✓	✓		84%	0%	16%	71%	0%	29%	6-7	0,34	0,58

All printed colours and textures only provide orientation and are not reference pattern.

Usable for	Roller / Vertical / Panel Track	Weight	420 g/m <sup>2</sup>
Colour Range	15	Thickness	0,50 mm
Composition	100 % PES	Moisture proofed	yes
Width	89 / 127 / 2300 / 3000 mm	PVC free	yes
Cutting Process	cold	OekoTex	yes
Processing Direction	warp & weft		



**Flame retardant**

DIN 4102, B1  
NF P 92-503-507,M1  
BS 5867 part 2  
UNI 8456-UNI 9174 C1  
EN 13773 class 1  
NFPA 701- USA



suitable for workstations



**D black-out**



Standard 100 by Oeko-Tex®

R = Reflection, T = Transmission, A = Absorption · All light & solar properties have been tested internally or externally · Gtot: measure total solar energy that passes through the glazing system and the fabric · Fc value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g · Gtot and Fc-value are calculated on the basis of a glass with an Ug-value of 1,2 and g-value of 0,59 according to DIN EN 14501 glass C · All technical properties are subjected to production-related deviations. All fabrics are in line with the REACH regulation.