



Lisboa

Number	Colour	89	Width mm			Light Properties			Solar Properties			Light Fastness	Gtot - value	FC - value
			127	2300	3000	R	T	A	R	T	A			
1021	white	✓	✓	✓	✓	84%	15%	1%	72%	16%	12%	6-7	0,34	0,58
2103	beige	✓	✓	✓	✓	79%	14%	7%	70%	16%	14%	6-7	0,34	0,58
9030	grey	✓	✓	✓	✓	55%	5%	40%	52%	7%	41%	6-7	0,40	0,68
9060	mouse grey	✓	✓	✓	✓	30%	0%	70%	29%	2%	69%	6-7	0,47	0,80
2272	sand	✓	✓	✓	✓	69%	9%	22%	64%	13%	23%	6-7	0,36	0,61
9163	black	✓	✓	✓		4%	2%	94%	3%	8%	89%	6-7	0,56	0,95
2071	cream	✓	✓	✓		70%	12%	18%	63%	15%	22%	6-7	0,37	0,63
4125	light green	✓	✓	✓		68%	9%	23%	60%	13%	27%	6-7	0,38	0,64
5049	blue	✓	✓	✓		31%	1%	68%	41%	6%	53%	6-7	0,44	0,75

All printed colours and textures only provide orientation, and are not reference pattern.

Usable for Roller / Vertical / Panel Track
 Colour Range 18
 Composition 100 % PES
 Width 89 / 127 / 2300 / 3000 mm
 Cutting Process cold
 Processing Direction warp & weft

Weight 220 g/m²
 Thickness 0,30 mm
 Moisture proofed yes
 PVC free yes
 OekoTex yes




Flame retardant

DIN 4102, B1
 NF P 92-503-507, M1
 BS 5867 part 2
 NFPA 701- USA



suitable for workstations



B semi-transparent



Standard 100 by Oeko-Tex®

R = Reflection, T = Transmission, A = Absorption · All light & solar properties have been tested internally or externally. · Gtot: measure total solar energy that passes through the glazing system and the fabric · Fc value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g · Gtot and Fc-value are calculated on the basis of a glass with an Ug-value of 1,2 and g-value of 0,59 according to DIN EN 14501 glass C. · All technical properties are subjected to production-related deviations. All fabrics are in line with the REACH regulation.