



PARIS OPAC


Number	Colour	Width mm		Light Properties			Solar Properties			Light Fastness	Gtot - value	FC - value
		2000	3000	R	T	A	R	T	A			
1079	white	✓	✓	84%	0%	16%	71%	0%	29%	6-7	0,34	0,58
2326	bleached sand	✓	✓	84%	0%	16%	71%	0%	29%	6-7	0,34	0,58
9058	anthracite	✓	✓	84%	0%	16%	71%	0%	29%	6-7	0,34	0,58
9199	flint grey	✓	✓	84%	0%	16%	71%	0%	29%	6-7	0,34	0,58
9092	black	✓	✓	84%	0%	16%	71%	0%	29%	6-7	0,34	0,58
4174	morning mist	✓		84%	0%	16%	71%	0%	29%	6-7	0,34	0,58

All printed colours and textures only provide orientation and are not reference pattern.

Usable for	Roller / Panel Track	Weight	290 g/m ²
Colour Range	24	Thickness	0,45 mm
Composition	100 % PES	Moisture proofed	yes
Width	2000 / 3000 mm	PVC free	yes
Cutting Process	cold	Halogen free	yes
Processing Direction	warp & weft	OekoTex	yes



suitable for Workstations



D black-out



by Gerhard van Cleve GmbH & Co.KG



Standard 100 by Oeko-Tex®

R = Reflection, T = Transmission, A = Absorption • All light & solar properties have been tested internally or externally. • Gtot: measure total solar energy that passes through the glazing system and the fabric • Fc value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g. • Gtot and Fc-value are calculated on the basis of a glass with an Ug-value of 1,2 and g-value of 0,59 according to DIN EN 14501 glass C. • All technical properties are subjected to production-related deviations. All fabrics are in line with the REACH regulation.